

[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)

[Advanced Search](#)

[Preferences](#)

The "AND" operator is unnecessary – we include all search terms by default. [\[details\]](#)

**Web Results 1 - 5 of about 6 for communication between ICE and microcontroller "in halt state" . (0.53 sec)**

Tip: Try removing quotes from your search to get more results.

**[PDF] AVR ICE 200 User Guide**

File Format: PDF/Adobe Acrobat

... I/O Continues to Operate in Halt State After a Break or Break Point. ...

The default **communication speed** between AVR Studio and the ICE200 is 19200 bps. ...

[www.atmel.com/dyn/resources/prod\\_documents/doc1413.pdf](http://www.atmel.com/dyn/resources/prod_documents/doc1413.pdf) - [Similar pages](#)

**[PDF] ICEPIC**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... particularly when compared to the cost of the PIC **microcontroller** ... If the processor is already in **HALT state**, the processor is reset, and put in halt ...

[www.okwelectronics.com/datasheets/ICEPIC\\_Man.pdf](http://www.okwelectronics.com/datasheets/ICEPIC_Man.pdf) - [Similar pages](#)

**STMicroelectronics | 16K/24K/32K ROM HCMOS MCU WITH ON-SCREEN ...**

... TLTEV (R246.3; Page 0) selects **between** the rising (if set) or falling (if ...

when the core is in **HALT state** (after a HALT instruction execution). ...

[www.st.com/stononline/books/ascii/docs/9885.htm](http://www.st.com/stonline/books/ascii/docs/9885.htm) - 345k - [Cached](#) - [Similar pages](#)

**STMicroelectronics | ST92163 - 8/16-BIT FULL SPEED USB MCU FOR ...**

... Enhanced USB Low-Speed and Full-Speed Interface on 8bit **Microcontroller Range** |

P811P ... **Communication Applications**. BroadCast, ST92163N4 ST92163R4 ...

[www.st.com/stononline/books/ascii/docs/5521.htm](http://www.st.com/stononline/books/ascii/docs/5521.htm) - 513k - [Cached](#) - [Similar pages](#)

**[PDF] GiN mbH Tiny-Module Host-Software Documentation Version 1.4**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... CAN identifiers 0x700 and 0x701 are used for the stream **communication**. ...

An application program running on a larger computer or **microcontroller**, ...

[www.gin.de/downloads/hostsw.pdf](http://www.gin.de/downloads/hostsw.pdf) - [Similar pages](#)

*In order to show you the most relevant results, we have omitted some entries very similar to the 5 already displayed.*

*If you like, you can [repeat the search with the omitted results included](#).*

New! Get email updates of [new web results for communication between ICE and microcontroller "in halt state"](#) with Google Web Alerts.

Free Google Desktop Search: Search your own computer. [Download now](#).

**Find:**  emails -  files -  chats -  web history -  media -  PDF

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google